

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: SENSOR-SAFE VALVE COVER AND OIL PAN OEM RTV .5OZ TB CG
Item No: 22072
Product Type: Elastomeric rubber

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	30-40	Not Listed	Not Listed
LIMESTONE 1317-65-3	30-40	Not Listed	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable)
POLYDIMETHYLSILOXANE 63148-62-9	10-20	Not Listed	Not Listed
MODIFIED SILICON DIOXIDE 68611-44-9	1-10	Not Listed	Not Listed
VINYL OXIMINOSILANE 2224-33-1	1-10	Not Listed	Not Listed
CARBON BLACK 1333-86-4	0.1-1.0	3.5 mg/m ³ TWA	3.5 mg/m ³ TWA
2-BUTANONE OXIME 96-29-7	****	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. ****When this product if exposed to moisture, butanone oxime may be formed. When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde. May be harmful if swallowed. May irritate lips, gums, tongue, mouth, nose and throat.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: ****Butanone oxime produced during curing is toxic and irritates eyes, nose and throat. Overexposure to the silane may cause coma and respiratory failure.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
CARBON BLACK 1333-86-4	0.1-1.0		Group A4 - Not classifiable as a human carcinogen	Group 2B; Monograph 65, 1996

Medical Conditions Recognized as Being Aggravated by Exposure: None known.

4. FIRST AID MEASURES

Ingestion: Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation develops or if breathing becomes difficult.

Skin Contact: Wipe off paste with paper towel or cloth. Wash exposed area with soap and water. Seek medical attention if irritation persists..

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): More than 200 degrees F. Method: Tag Closed Cup
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

5. FIRE FIGHTING MEASURES

Special Fire-Fighting Procedures:	Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
Hazardous Products of Combustion:	Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Oxides of carbon, Formaldehyde
Unusual Fire/Explosion Hazards:	None.
Lower Explosive Limit:	Not determined
Upper Explosive Limit:	Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:	Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.
--------------------------	--

7. HANDLING AND STORAGE

Storage:	Store in a dry area below 90 degrees F. Keep container closed when not in use.
Handling:	Avoid contact with skin and eyes. Do not inhale vapors.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Safety glasses Avoid contact lenses.
Skin:	Rubber or plastic gloves.
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection:	Not normally necessary. In case of insufficient ventilation, wear suitable respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Black paste
Odor:	MILD
Boiling Point:	Not applicable, polymeric material
pH:	Does not apply
Solubility in Water:	Polymerized
Specific Gravity:	1.35
VOC Content(Wt.%):	5.4% by weight
Vapor Pressure:	Less than 5 mm Hg @ 80 degrees F.
Vapor Density (Air=1):	3.0
Evaporation Rate:	Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable at normal conditions
Hazardous Polymerization:	WILL NOT OCCUR.
Incompatibilities:	Polymerized by contact with moisture., Strong oxidizers, Acids, Iron
Conditions to Avoid:	Exposure to moisture
Hazardous Products of Combustion:	Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Oxides of carbon, Formaldehyde

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:	Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number:	NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name:	Unrestricted
---------------------------	--------------

Product Name: SENSOR-SAFE VALVE COVER AND OIL
PAN OEM RTV .5OZ TB CG

Item No: 22072

Hazard Class: None
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Unrestricted
Class or Division: None
UN/NA Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: February/01/2007
Revision Number: 2