

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 80265 FIBERGLASS PATCH KIT PART 1
Item No: 202002R
Product Type: Epoxy resin

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL:
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN 25068-38-6	>60	Not listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. May cause skin sensitization.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: May cause pain, redness or swelling of the eyes and excessive blinking and tear production. Repeated skin contact may cause allergic skin reactions. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. Ingestion may cause nausea and vomiting.

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >400°F PMCC
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Material will not burn unless preheated. Firefighters should wear self-contained breathing apparatus. Use water spray to cool exposed containers.
Hazardous Products of Combustion: Oxides of carbon, Aldehydes, Acid vapors
Unusual Fire/Explosion Hazards: May decompose above 300 degrees F.; may polymerize above 500 degrees F. in which case closed containers may rupture or explode. Fumes and vapor from thermal and chemical decomposition vary in composition and toxicity. Do not breathe fumes.

Lower Explosive Limit: Not determined
Upper Explosive Limit: Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Prevent from entering waterways or sewers.

7. HANDLING AND STORAGE

Storage: Store in a cool, dry area. Store away from heat.
Handling: Avoid contact with vapors from heated material. Avoid contact with skin and eyes. Wash thoroughly after handling. Discard contaminated leather gloves and shoes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended. Wash contaminated clothing before re-use.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: Not required under normal use. An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear viscous liquid
Odor: Slight
Boiling Point: >500°F
pH: Neutral
Solubility in Water: Negligible
Specific Gravity: 1.17
VOC Content(Wt.%): 0
Vapor Pressure: 0.03 mmHg @ 171°F
Vapor Density (Air=1): >1
Evaporation Rate: <1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: STABLE
Hazardous Polymerization: WILL NOT OCCUR
Incompatibilities: Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines)
Conditions to Avoid: Heat
Hazardous Products of Combustion: Oxides of carbon, Aldehydes, Acid vapors

11. TOXICOLOGICAL INFORMATION

Oral LD50 (rat) = 11.4 g/kg
Dermal LD50 (rabbit) = >20 ml/kg
Inhalation LC50 (rat) = no deaths (4h)
IARC Group 3; Not classifiable as a carcinogen

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted
Hazard Class: None
UN/ID Number: None

IATA

Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

Marine Pollutant: None

Product Name: 80265 FIBERGLASS PATCH KIT PART 1

Item No: 202002R

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: July/25/2008

Revision 3

Number:

Telephone No.: 1-87-Permatex (877) 376-2839

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924
International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 80265 FIBERGLASS PATCH KIT PART 2
Item No: PTX203004R
Product Type: Curing agent

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL:
NONYLPHENOL 25154-52-3	75-85	Not listed	Not Listed
2-PIPERAZINE-1-YLETHYLAMINE 140-31-8	15-25	Not listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May be harmful if swallowed. Harmful if absorbed through the skin. The aminophenol can cause severe irritation and may be corrosive on prolonged contact. It may be a sensitizer. It can also be corrosive to eye tissue, leading to permanent injury including blindness. It may irritate the respiratory tract and may cause delayed lung damage upon overexposure to fumes or vapors. It can cause fatigue, muscular weakness, labored breathing or gastrointestinal irritation if swallowed .

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Can cause severe and painful burns on contact to eyes, skin and if taken internally. Repeated skin contact may cause allergic skin reactions.

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product. Persons with respiratory problems such as emphysema and asthma should avoid inhalation.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Wash off with soap and water. Cover wound with sterile dressing. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): 214°F CC

Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Alcohol foam

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Use water spray to cool exposed containers.

Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen, Amines, Ammonia

Unusual Fire/Explosion Hazards: Irritating or toxic gases or fumes may be generated by thermal decomposition or combustion.

Lower Explosive Limit: Not determined.

Upper Explosive Limit: Not determined.

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store in a cool, dry area. Keep away from oxidizers.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Discard contaminated leather gloves and shoes. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Do not mix with sodium nitrite or other nitrosating agents as cancer-causing nitrosamines could be formed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber liquid
Odor: AMMONIA
Boiling Point: >390°F
pH: Alkaline (5% solution or slurry in water)
Solubility in Water: Soluble
Specific Gravity: 0.97
VOC Content(Wt.%): 0
Vapor Pressure: <1 mmHg @ 70°F
Vapor Density (Air=1): Heavier than air
Evaporation Rate: <1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: STABLE
Hazardous Polymerization: WILL NOT OCCUR
Incompatibilities: Strong oxidizers, acids, chlorinated hydrocarbons., Active metals, Strong oxidizers such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite, Peroxides
Conditions to Avoid: Heat
Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen, Amines, Ammonia

11. TOXICOLOGICAL INFORMATION

Oral LD50 (rat) = 1620 mg/kg
Dermal LD50 (rabbit) = >1000 mg/kg

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
UN/ID Number: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/ID Number: ID 8000

IMDG

Proper Shipping: Corrosive liquids, basic, organic, n.o.s. (N-aminoethylpiperazine, nonylphenol)

Product Name: 80265 FIBERGLASS PATCH KIT PART
2

Item No.: PTX203004R

Hazard Class: Class 8 PGIII
UN Number: UN 3267

Marine Pollutant: Nonylphenol

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

None

CALIFORNIA PROP 65:

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 3, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 3, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: July/25/2008

Revision Number: 2

Telephone No.: 1-87-Permatex (877) 376-2839