

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 161DA PAINT STRIPPER 12 OZ AE
Item No: 80577
Product Type: Aerosol cleaner

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH TLV: TWA	OSHA PEL:
DICHLOROMETHANE 75-09-2	60-100	50 ppm TWA; 174 mg/m ³ TWA	25 ppm TWA; 125 ppm STEL (15 min. TWA)
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	10-30	1000 ppm TWA	Not Listed
METHANOL 67-56-1	<7	200 ppm TWA; 262 mg/m ³ TWA	200 ppm TWA; 260 mg/m ³ TWA

3. HAZARDS IDENTIFICATION

Toxicity: Harmful if inhaled. Harmful if swallowed. May cause eye, skin and respiratory irritation. Vapors are anesthetic in high concentrations. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as "solvent" or "painter's syndrome"). Symptoms include fatigue, concentration difficulties, anxiety, depression, rapid mood swings, and short-term memory loss. Prolonged exposure may cause liver and kidney effects and may affect the central nervous system. Methylene chloride will have an effect on the cardiovascular system. Inhalation of high concentrations of Methylene chloride over long periods of time has caused cancer in laboratory animals. Deliberately concentrating and inhaling the vapor may be harmful or fatal.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. Inhaling may cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression. Overexposure may cause eye and skin redness.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
DICHLOROMETHANE 75-09-2	60-100	Group 2: Suspect Carcinogen	A3 - Animal Carcinogen	Group 2B: Monograph 41, Supplement 7, Monograph 71; 1998

Medical Conditions Recognized as Being Aggravated by Exposure: Heart disease, respiratory disorders, liver and kidney diseases, amenia, rhythm disorders of the heart.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If not breathing, give artificial respiration. Obtain medical attention.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): Flammable per flame projection

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products of Combustion: Hydrogen chloride, Carbon Monoxide and Carbon Dioxide.

5. FIRE FIGHTING MEASURES

Unusual Fire/Explosion Hazards:

Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.

Lower Explosive Limit:

Not determined

Upper Explosive Limit:

Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.

Handling:

Avoid contact with skin and eyes. Do not use near heat, sparks or open flame. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Use only in a well ventilated area. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses

Skin:

Neoprene, rubber or butyl rubber gloves.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection:

An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Clear liquid

Odor:

Ether odor

Boiling Point:

>100°F

pH:

Not applicable

Solubility in Water:

Partial

Specific Gravity:

1.17-1.27

VOC Content(Wt.%):

24% by weight

Vapor Pressure:

Not Determined

Vapor Density (Air=1):

Heavier than air

Evaporation Rate:

Faster than ether

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

WILL NOT OCCUR.

Incompatibilities:

Strong oxidizers, Active metals

Conditions to Avoid:

Keep away from heat, sparks and open flame

Hazardous Products of Combustion:

Hydrogen chloride, Carbon Monoxide and Carbon Dioxide.

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:

Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number:

D001/F002 - Hazardous waste per 40CFR 261.21 and 261.31 (Methylene Chloride)

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

14. TRANSPORTATION INFORMATION

DOT Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Class or Division: Division 2.1, Subsidiary Risk 6.1
UN/NA Number: UN 1950

IMDG

Proper Shipping: Aerosols
Hazard Class: Class 2, 6.1
UN Number: UN 1950

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

DICHLOROMETHANE, METHANOL

CALIFORNIA PROP 65:

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 3, FLAMMABILITY 3, REACTIVITY 0

Estimated HMIS Classification: HEALTH 3, FLAMMABILITY 3, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: February/05/2007
Revision Number: 1