

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 77BR ULTRA BLUE RTV SILICONE GASKET MAKER 3.35OZ TB CG
Item No: 81724
Product Type: Elastomeric rubber

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH TLV: TWA	OSHA PEL:
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	20-40	Not listed	Not Listed
CALCIUM CARBONATE 471-34-1	20-40	10 mg/m ³ particulate TWA	Not Listed
LIMESTONE 1317-65-3	10-30	Not listed	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable)
POLYBUTYLENE RESIN 9003-29-6	10-30	Not listed	Not Listed
VINYL OXIMINOSILANE 2224-33-1	<5	Not listed	Not Listed
STEARIC ACID 57-11-4	<5	Not listed	Not Listed
2-BUTANONE OXIME 96-29-7	****	Not listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. May irritate respiratory system upon frequent or prolonged use. May irritate lips, gums, tongue, mouth, nose and throat. ****When this product is exposed to moisture, butanone oxime may be formed.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: ****Butanone oxime produced during curing is toxic and irritates eyes, nose and throat. Overexposure to the silane may cause coma and respiratory failure.

Medical Conditions Recognized as Being Aggravated by Exposure: None known.

4. FIRST AID MEASURES

Ingestion: Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

Skin Contact: Wipe off material with paper towel or cloth. Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): >200°F TCC

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products of Combustion: Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Oxides of carbon, Formaldehyde

Unusual Fire/Explosion Hazards: None

Lower Explosive Limit: Not determined

Upper Explosive Limit: Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage: Store away from water or moisture.

Handling: Avoid contact with skin and eyes. Do not wear contact lenses. Use only in a well ventilated area. Do not take internally.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.

Skin: Rubber or plastic gloves.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection: Not required under normal use. In case of insufficient ventilation, wear suitable respiratory equipment.

Comments: When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Blue paste

Odor: MILD

Boiling Point: Not applicable, polymeric material

pH: Does not apply

Solubility in Water: Polymerized

Specific Gravity: 1.37

VOC Content(Wt.%): 3.8% by weight

Vapor Pressure: <5 mm Hg @ 80°F

Vapor Density (Air=1): 3.0

Evaporation Rate: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization: WILL NOT OCCUR.

Incompatibilities: Polymerized by contact with moisture., Strong oxidizers, Acids, Iron

Conditions to Avoid: Exposure to moisture

Hazardous Products of Combustion: Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Oxides of carbon, Formaldehyde

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted

Hazard Class: None

UN/ID Number: None

Marine Pollutant: None

Product Name: 77BR ULTRA BLUE RTV SILICONE
GASKET MAKER 3.35OZ TB CG

Item No: 81724

IATA

Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: April/18/2008

Revision 5

Number:

Telephone No.: 1-87-Permatex (877) 376-2839