

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: COLD GALVANIZING COMPOUND 15OZ AE
Item No: 82039
Product Type: Aerosol coating

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
ACETONE 67-64-1	10-30	500 ppm TWA; 1188 mg/m ³ TWA	1000 ppm TWA; 2400 mg/m ³ TWA
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	10-30	1000 ppm TWA	Not Listed
TOLUENE 108-88-3	5-15	50 ppm TWA	200 ppm TWA; C 300 ppm
XYLENE 1330-20-7	1-10	100 ppm TWA; 434 mg/m ³ TWA	100 ppm TWA; 435 mg/m ³ TWA
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. 64742-88-7	0.5-5.0	Not Listed	400 ppm TWA; 1600 mg/m ³ dust

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Intentional misuse by concentrating and inhaling the vapor may be harmful or fatal.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.
Signs and Symptoms of Exposure: Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. May cause redness to eyes and irritation to nasal passages.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
ACETONE 67-64-1	10-30	Not known	A4 - Not Classifiable as a Human Carcinogen	Not known
TOLUENE 108-88-3	5-15	male rat-no evidence; female rat-no evidence	A4 - Not Classifiable as a Human Carcinogen	Group 3; Vol. 71, pg. 829, 1999
XYLENE 1330-20-7	1-10	male rat-no evidence; female rat-no evidence; male mice-no evidence; female mice-no evidence	A4 - Not Classifiable as a Human Carcinogen	Group 3; Vol. 71, pg 1189, 1999

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention..
Inhalation: Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed. Obtain medical attention.
Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): -156 degrees F. Based on propellant
Recommended Extinguishing Media: Water fog, carbon dioxide, foam, dry chemical.

Special Fire-Fighting Procedures:

Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Oxides of carbon. Irritating vapors.

Hazardous Products Formed by Fire or Thermal Decomposition:

Unusual Fire/Explosion Hazards:

Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.

Lower Explosive Limit:

1.9

Upper Explosive Limit:

9.5

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F. Exposure to high temperatures may cause container to burst.

Handling:

Avoid contact with skin and eyes. Do not inhale vapors. Do not puncture or incinerate container. Do not use near heat, sparks or open flame. Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances, and other sources of ignition. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Use only in a well ventilated area. Vapors may accumulate readily and may ignite explosively. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses.

Skin:

Rubber or plastic gloves

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits during the use of this product.

Respiratory Protection:

An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Gray liquid

Odor:

SOLVENT

Boiling Point (°F):

>100 degrees F.

pH:

Does not apply

Solubility in Water:

Nil

Specific Gravity:

1.8-2.0 g/ml

VOC Content(Wt.%):

36.1% by weight

Vapor Pressure:

65-75 psig

Vapor Density (Air=1):

Heavier than air

Evaporation Rate:

<1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

WILL NOT OCCUR

Incompatibilities:

Acids, Strong oxidizers.

Conditions to Avoid:

Keep away from heat, sparks and open flame.

Hazardous Products Formed by Fire or Thermal Decomposition:

Oxides of carbon. Irritating vapors.

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/NA Number: ID 8000

IMDG

Proper Shipping: Aerosols, Limited Quantity
Hazard Class: Class 2.1
UN Number: UN 1950

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

SARA 313 Information
XYLENE, TOLUENE

CALIFORNIA PROP 65:

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA Inventory Status:

Listed on Inventory: **YES** All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 4, REACTIVITY 0
Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 4, PHYSICAL HAZARD 0
NFPA is a registered trademark of the National Fire Protection Assn.
HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA
06106
Telephone Number: 1-87-Permatex (877) 376-2839

Revision Date: 03/28/2005
Revision Number: 2